
North America's Leader in Hazardous Material Information Management
1905 Aston Avenue, Carlsbad, CA 92008
Phone (800) 451-8346 Fax (760) 602-8888

MSDS PRODUCT INFORMATION

Date: 10/07/2005
To: MSDS Requester
From: 3E Company
Subject: The MSDS you have requested

☐ MSDS NOT REQUIRED

In response to your request for a Material Safety Data Sheet, according to the OSHA Hazard Communication Standard (Right-to-Know), the following item is an article. Articles are defined in 29 CFR 1910.1200(c). Products such as Drugs, cosmetics, food, or alcoholic beverages, wood or wood products, and tobacco or tobacco products, as defined in 29 CFR 1910.1200(b)(6), are exempt from the Hazard Communication Standard. Items that are considered articles, as defined in 29 CFR 1910.1200(c), are also exempt from this Standard. Therefore, the manufacturer is not required to provide an MSDS for this product.

☒ MSDS DISCONTINUED PRODUCT

In response to your request for a Material Safety Data Sheet, the manufacturer has discontinued the product listed below. The MSDS Attached is the most current version, or an MSDS is no longer available.

☐ MSDS BEST COPY AVAILABLE

The MSDS attached is the best copy available from the manufacturer.

☐ MANUFACTURER NO LONGER IN BUSINESS

In response to your request for a Material Safety Data Sheet, a current MSDS could not be obtained for this product. It has been determined that the manufacturer listed below is no longer in business. A current address and phone number could not be located.

Manufacturer: Franklin International
Product Name: Bruce Wood Filler (DISCONTINUED)

** MATERIAL SAFETY DATA SHEET **

Information Phone # : (800)-347-4583

FRANKLIN INTERNATIONAL
2020 BRUCK STREET
COLUMBUS, OH 43207

Latest Revision Date...07/05/95
Print Date.....12/06/96
EMERGENCY PHONE NUMBER: 1-614-445-1411

BRUCE LATEX WOOD FILLER

SECTION 1 PRODUCT IDENTIFICATION

PRODUCT NAME..... BRUCE WOOD FILLER (ALL COLORS)
CHEMICAL FAMILY..... Polymer dispersed in water with inert re-
inforcing material.
MFG.CODE..... 3441, 3442, 3443, 3444, 3445, 3446, 3447,
3448, 3449, 3453, 3454, 3455, 3456, 3457
SALES CODE(S)..... 151113, 151118, 151123, 151128, 151133,
151138, 151143, 151148, 151153, 151158,
151163, 151168, 151173, 151178, 151183,
151188, 151193, 151198, 151213, 151218,
151223, 151228, 151233, 151238, 151243,
151248, 151253, 151258
DIVISION..... Construction Adhesives & Sealants

SECTION 2 HAZARDOUS INGREDIENTS

CHEMICAL NAME(S)	CAS NUMBER	% WT	OSHA TWA	OSHA Ceiling	OSHA STEL	ACGIH TLV	ACGIH STEL	SEC.313
VINYL ACETATE	108-05-4	.04	10 ppm	NA	20 ppm	10 ppm	20 ppm	Yes
ETHYLENE GLYCOL	107-21-1	0.7-6.8	50 ppm	50 ppm	NA	50 ppm	NA	Yes

SECTION 3 PHYSICAL DATA (TYPICAL)

BOILING POINT..... ca 212°F
VISCOSITY (cps.)..... 100,000
VAPOR DENSITY (Air = 1)..... >1
SOLUBILITY IN WATER..... Dispersible
SPECIFIC GRAVITY (HOH = 1)..... 1.5 - 1.6
PERCENT VOLATILE (Wt.%)..... 30.3 - 33.3
EVAPORATION RATE (N-BUTYL = 1).. <1
pH..... 7.5 - 8.5
APPEARANCE..... Paste, variety of colors
ODOR..... Mild odor

SECTION 4 FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Test Method)..... >200°F (Setaflash)
FLAMMABILITY LIMITS..... NA
EXTINGUISHING MEDIA..... Water for dried adhesive
SPECIAL FIRE FIGHTING PROCEDURES Wear MSHA/NIOSH approved self contained
breathing apparatus (schedule 13)

BRUCE LATEX WOOD FILLER

SECTION 4

FIRE AND EXPLOSION HAZARD DATA

CONT'D

UNUSUAL FIRE & EXPLOSION HAZARDS None

SECTION 5

HEALTH HAZARD DATA

ROUTES OF ENTRY..... INGESTION: No
INHALATION: Yes
SKIN: No

POSSIBLE EFFECTS OF EXPOSURE....

SKIN CONTACT..... Will not be absorbed through skin. In rare cases may cause skin rash. Irritation.

EYE CONTACT..... Irritation

INHALATION..... No known adverse effects from the use of this product at room temperature. Heating of this product may result in increased exposure to residual monomer vapors. Inhalation of vapors can cause irritation of the upper respiratory. Overexposure may cause irritation of the upper respiratory tract and dizziness.

INGESTION..... Gastrointestinal irritation

MED.COND.AGGRAVATED BY EXPOSURE.

CARCINOGENICITY..... IARC Monographs: Yes
NTP: No
OSHA Regulated: No

NOTE..... IARC has listed vinyl acetate as possibly carcinogenic to humans (based on inadequate human data & limited animal data). Available epidemiologic studies do not confirm an increased risk of cancer in exposed humans; available evidence suggest that the agent is not likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure; A3, animal carcinogen, ACGIH.

REPRODUCTIVE TOXICITY..... Not applicable

WARNING..... Not applicable

SECTION 6

EMERGENCY AND FIRST AID PROCEDURES

CONSULT PHYSICIAN IN ALL CASES

BRUCE LATEX WOOD FILLER

SECTION 6

EMERGENCY AND FIRST AID PROCEDURES

CONT'D

SKIN..... Wash with soap and water.
EYES..... Rinse with running water for 15 minutes.
INGESTION..... Do not induce vomiting.
INHALATION..... Remove individual to fresh air.

SECTION 7

REACTIVITY DATA

PRODUCT STABILITY..... Stable
Conditions to Avoid..... None
CHEMICAL INCOMPATIBILITY..... Strong acids and strong bases

HAZARDOUS DECOMPOSITION PRODUCTS Oxides of carbon and monomer when burned
HAZARDOUS POLYMERIZATION..... Will not occur
Conditions to Avoid..... None

SECTION 8

SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION..... Wear suitable NIOSH/MSHA approved respirator where exposure limits are exceeded.

VENTILATION - Local Exhaust..... At point where product is dried. Standard plant ventilation otherwise.
- Mechanical (Gen).. Yes
- Special..... No
- Other..... No
SKIN PROTECTION..... Where repeated and prolonged contact can occur, the use of impervious gloves is recommended.

EYE PROTECTION..... Splashproof safety eye protection.
OTHER PROTECTIVE EQUIPMENT..... None

SECTION 9

SPILL OR LEAK PROCEDURES

SPILL OR LEAK PROCEDURES..... Clean up with suitable absorbent and place in an approved container. If product has dried, scrape up and place in approved container.

BRUCE LATEX WOOD FILLER

SECTION 9

SPILL OR LEAK PROCEDURES

CONT'D

WASTE DISPOSAL METHOD..... Disposal of product should comply with all applicable federal, state and local regulations.

CONTAINER DISPOSAL..... Disposal of container should comply with all applicable federal, state and local regulations.

SECTION 10

SPECIAL PRECAUTIONS

SPECIAL HANDLING..... Store above 0°F

KEEP FROM FREEZING..... Yes

KEEP OUT OF REACH OF CHILDREN... Yes

SECTION 11

REGULATORY INFORMATION

NEW JERSEY..... Ethylene glycol 107-21-1
Calcium carbonate 1317-65-3
Talc 14807-96-6
Water 7732-18-5
Polyvinyl acetate emulsion 24980-61-8

CALIFORNIA PROPOSITION 65..... The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product may contain the following chemicals, "known to the State to cause cancer": [acrylamide 79-06-1, acetaldehyde 75-07-0 and ethylene oxide 75-21-8 (Butterscotch, Caramel, Chestnut, Creme, Desert, Glacial White, Gunstock, Ivory White, Natural, Quartz, Toast, Vaintage Brown, Winter White)]

[acrylamide 79-06-1, acetaldehyde 75-07-0 and talc 14807-96-6 (Auburn, Peachtree, Sedona, Parchment)]

[acrylamide 79-06-1, acetaldehyde 75-07-0 and carbon black 1333-86-4 (Driftwood)].

CALIFORNIA RULE 1168..... Calculated VOC: 1.6 g/l

HMIS RATING..... Health 1
Flammability 1
Reactivity 0
Protective Equipment See Section 8

BRUCE LATEX WOOD FILLER

SECTION 12

SUPPLIER INFORMATION

Notice: While the information and recommendations set forth herein are believed to be accurate as of the data hereof, Franklin International makes no warranty express or implied, with respect thereto and disclaims all liability from reliance thereon.